


With PATENT PENDIING Technology


**Control Panel** 

Easily to Carry!

Recommended UseRecommended use(s) of on-board duplex GFCI are shown. Note: Standard 115VAC electrical outlets.













Half the height of standard carpet dryers ▶

# Operating Position.



▲ Horizontal



▲ Stand (Stairwells/Wall Drying)



▲ Left (Wall Drying)



Right(Wall Drying)



Vertical(Walls/Cellings)

Applications	Zeus 900
Restoration Works	4
Confined Aears	✓
Constrcution Sites	✓
Crawl Space&Basement	✓
Electric, Gas, Water Utillities	✓
Fire Departments	✓
Industrial Cleaning	<b>≠</b>
Manholes	<b>4</b>

Applications	Zeus 900
MunicipalIties	1
Mines&Shafts	4
Tunnels	4
Tank Cleaning	4
Telephone Crews	4
Welding Booths	4
Storage Areas	4
Vaul Cleaning	4

# Applications

Drying and clear the air for workers or homeowners, especially with asthma or allergies. The kit features a HEPA media filter to minimize dust and particulates during restoration.

Compact size makes Zeus 900 the most compact and portable fan in its class. The rugged molded handle gives you the solid control during packing and unpacking lots of air movers. Its easy-winding cord wrap and multiple security options makes it safe and easy for transport. Zeus 900 is rock solid when stacked for transport as its mold features. Zeus 900 is the most versatile air movement system available. With its patent pending, the Zeus 900 can deliver airflow of 950 cfm. The unit is stable in operation in all 5 drying positions with flexibility. Wherever adverse environmental pose a threat to health, safety and efficiency, Zeus 900 is the right solution for improving air quality.

Zeus 900 has the safest fan in its class as it has GFCI

convenience receptacle which protects not only connected loads, but onboard components. This is unlike common fans on the market that require external GFCI protection.



ALORAIR Radial Air Mover With PATENT PENDIING Technology

# ZEUS SOO



Half The Size **Ultra-Low Amps** 5-position Versatility **Ultra Secure Stacking** 







### PROVEN PERFORMANCE

The ZEUS 900 features focused airstream of 950 cfm and a lightweight stackable designed to fit in vehicle space, on-board duplex GFIC outlet, circuit breaker, and superior cord management.

The ZEUS 900, half the height of standard carpet dryers and draws just 1.9 amps! With the ZEUS 900's high velocity airflow, you can rapidly dry the largest area or tackle any problems with five versatile positions.





Features	ZEUS 900
Less than 1.9 amps	<b>4</b>
Duct at Outlet	4
Power-on indicator light	4
Automatic hour meter displays site run time	4
Circuit breaker protects air mover and attached devices and prevents nuisance visits to the junction box	4
GFCI promotes operator safety in wet applications	4
20 ft AC cord with cord management	4
Units interlock for easy stacking in storage and handling	4
Daisy chain up to 6 fans on a single 15 Amp circuit	4
Over 950 CFM	4
Maintenance free Bearing Motor	4
Flex handle	4
5 drying positions to maximize flexibility	<b>*</b>
LCD Dispaly	<b>≠</b>

Cuacifications	75110 000
Specifications	ZEUS 900
Fan	6 Blades
Control	On/Off Switch With Variable Speed
Voltage	115 VAC
Current	1.9 Amps (High Speed)
Cord	20 ft Power Cord
Outlet	15A UL Rated GFCI Duplex Receptacle
Air flow	Approximately 950
Sound Pressure Leve	<69DBA
Wieght	19.2.lbs(9.0KG)
Warranty	1 Year - 100% parts and labor(all components) 2 Year - 100% parts only (all components) 3 -7Year(s) - Materials and workmanship of the housing only.
Dim(W*H*D)	17.4"*9.85"*21.65"
Safety	ETL CE TUV SGS
Loading quantity	20":378Sets/40":820Sets/40"HQ:924Sets

## Key Design Features —



- Half the height of standard carpet dryers and the draws just below 1.9 Amaps
- Great chain up to 6 fans on a single 15 Amp circuit
- Greater air velocities than competitive products
- Maintenance free Bearing Motor, Low noise, quiet operation

- Onboard circuit breaker and branch protection GFCI
- Ultra secure stacking and cord wrap
- Lightweight and compact Linear Low Density Polyethylene (LLDP) housing is washable, chemical resistant and stacks for storage.

## Replacement Parts —



TIf: 33 47 01 00

www.bedre-inneklima.no



Tlf. 33 47 01 00